











No	Product name	Fields of application	Pic.	Net weight	Units/pck	Price from 5000
Products in cartridges, for indoor and outdoor works						
1	Spray foam «FOAM» TM "elite construction"	For insulation of holes, gaps and joints during windows or doors installation, as well as in roofing joints and insulation materials. Sealing passes around pipes and mounting of construction parts. Can be also used for creating soundproof screens. For professionals. (Manual use).		750 ml	12	
2	Silicone sealant «SILICONE» TM "elite construction"	For long lasting insulation of seams and joints between indoor and outdoor decoration elements, wall and floor ceramic tiles, window and door frames, during glazing, and for holes and cracks filling. Colors available: transparent and white.		300 ml	24	
3	"Acrylin - 4" Acrylic Sealant	For sealing joints and seams of window and door frames, baseboards, windowsills. For filling cracks in concrete, plaster, masonry, gypsum, wood. Colors available: white.		400 g	24	
4	"Acrylin - 5" Glue-sealant 2 in 1 acrylic white	For long lasting sealing and protection of joints and seams (window frames, door, baseboards, windowsills etc.). For filling- in voids, cracks, holes in concrete, plaster, gypsum, timber. For gluing products made from polyurethane, polystyrene, dry wall, wood, cork, cloth, paper. Solvent free. After drying forms a durable, transparent, elastic, weatherproof, mechanic stress and moisture resistant bond.		400 ml	24	
5	Acrylic Glue-sealant 2 in 1 "Power" Transparent			300 ml	24	
6	Adhesive for styrofoam elements "Decor"	For mounting decorative tiles and elements made from polysterene foam (styrofoam), dry wall, wooden articles. Suitable for all mineral surfaces and dry wall. Colors available: white.		400 g	24	
7	"Drevo - Strong - D3" Adhesive for all types of wooden surfaces Moisture resistance D3	For professional use. For furniture, windows and other structures; parquet, plywood, fiberboard, particle board, veneer, cardboard. High adhesion to wooden surfaces, subjected to static and dynamic loads. For indoor works only.		300 ml	24	
8	"Liquid nails" universal polymeric adhesive Moisture resistance D4	Polymeric, universal, frost, heat and moisture-resistant, fast hardening. For attaching decorative elements like: crown moulding, baseboards and tiles made from polysterene foam, dry wall, ceramic tiles, parquet, linoleum, wood. Colors available: white.		280 ml	24	
9	Liquid nails - adhesive "Acrylin - 3"	Highly adhesive. For attaching decorative elements and tiles made from polystyrene foam, plastic, dry wall, wood, laminate floor, parquet, particle board, PVC, linoleum. Colors available: white.		400 g	24	
10	Adhesive for polyurithane products "Strong Contact"	Extra strong. Fine adhesion to smooth and rough surfaces. Resistant to weather and temperature changes. Acts as super glue for decorative elements made from polyurithane, polystyrene foam and dry wall. Colors available: white.		400 g	24	



11	Adhesion for decorative stone "Acrylin-5"	SUPER ADHESION! For long lasting and durable bonding of natural and artificial decorative stone onto a different types of surfaces (mineral, wooden, OSB, dry walls, metal). For decorative stone cladding of electrical, bioethanol and classic fireplaces (without direct contact of decoration elements and the adhesive joint with the flame). For filling seams between decorative stones. Does not flow down from vertical surfaces. Humidity resistance - D3. No solvents added. Odorless. Colors available: white.		400 g	24	
12	Antifungal filler - restorer "Seam - 2"	For filling joints between ceramic and marble tiles, also for recovery of old and aging joints. Less susceptible to pollution and efflorescence. Stable to mechanical stress. Elastic, water resistant. Colors available: snow white.		400 g	24	

READY MIXED COMPOUNDS

13	"HATCH - 4" frost-resistant liquid wood (putty)	For leveling and embedding of deepenings, gaps, cracks, on wooden, concreted, plastered surfaces. For restoration of molded and wooden products, insulation of window frames. For indoor and outdoor works.		0,35 kg plastic can	45	
----	---	---	---	---------------------	----	--

STYRENE - ACRYLIC WALL FILLERS


14	"Garant - 1" start wall filler, enforced	Acrylic - Styrene. Non shrinking. For smoothing of mineral and wooden surfaces: plaster, foam concrete, concrete, brick, dry wall, plywood, particle board, fiberboard, OSB, etc. Can be used for filling and fixing cracks and other minor defects, for grouting seams between dry walls. Easy to apply on surfaces painted with alkyd enamel. For indoor and outdoor works. Colors available: white.		0,4 kg	36	
				0,7 kg	24	
				1,5 kg	12	
				3,5 kg	1	
				60 kg	1	
15	"Garant - 2" finish wall filler	For high quality, thin-layered smoothing of walls and ceilings, on mineral surfaces made of: plaster, foam concrete, concrete, brick, dry wall, plywood, particle board, fiberboard and OSB. After drying forms snow-white and ideally smooth surface, suitable for further decoration. For indoor works only. Colors available: snow white.		0,4 kg	36	
				0,7 kg	24	
				1,5 kg	12	
				3,5 kg	1	
				8 kg	1	
15 kg	1					
60 kg	1					
16	"Garant - 3" multipurpose, enforced, moisture resistant wall filler	For high quality, thin-layered smoothing of walls and ceilings in areas with high operational loads: bathrooms, kitchens, mud rooms, living rooms, offices, educational institutions, hospitals, restaurants and etc. On mineral surfaces made from: foam concrete, concrete, plaster, dry wall, plywood, particle board, fiberboard and OSB. Easily sandable. For indoor and outdoor works. Colors available: snow white.		0,4 kg	36	
				0,7 kg	24	
				1,5 kg	12	
				3,5 kg	1	
				60 kg	1	
17	"Garant - 4" highly durable, enforced, wood filler	Acrylic. For smoothing and filling gaps on wooden and mineral surfaces: plywood, particle board, fiberboard, plaster, brick, concrete, etc. Also can be applied on surfaces painted with enamel and oil based paints. Wall filler's durability allows it to be used in areas exposed to high humidity and mechanical stress (floors, windows, doors, outdoor furniture, etc). For indoor and outdoor works. Colors available: pine, oak and white.		0,4 kg	45	
				0,7 kg	24	
				1,5 kg	12	
				3,5 kg	1	
				60 kg	1	
18	SALE! "Garant - 5" smooth wood filler finish abrasion resistant	Professional wood filler for ultra smooth finish for furniture, doors, wooden walls and ceilings. For obtaining a perfectly smooth and flat surface. Excellent adhesion to the surface. Wood filler is wear-resistant, elastic, vapor permeable, easy to apply and sand. Short drying time (less than 2h.) Can be used in premises with any humidity. For indoor works. Colors available: pine, oak and white.		0,4 kg	45	
				0,7 kg	24	
				1,5 kg	12	
				3,5 kg	1	
19	"Garant - 6" decorative	For creating decorative and protective, thin layered structure. After drying, plaster forms weatherproof marble chip coat.				





	marble chip plaster	Available plaster colors: white, pink, cream, red, dark red, maroon, light yellow, light green, dark green, grey and black. For indoor and outdoor decoration.		5 kg	1	
				15 kg	1	
20	"Garant - 7" decorative plaster	For creating structural surface coating on mineral surfaces, dry wall, styrene foam tiles. Allows different texture creation. After drying, forms durable weatherproof layer. For indoor and outdoor works. Colors available: white.		3,5 kg	4	
				8 kg	1	
				15 kg	1	









ACRYLIC PRIMERS






21	"Classic - 3" Deep-penetrating universal primer	For strengthening weak surfaces, increasing wear resistance and adhesion between the surface and coating. Surfaces: lightweight concrete, plaster, brickwork, gypsum etc. For indoor and outdoor works.		0,9 l	15	
				5 l	1	
				10 l	1	
22	"Classic-3" Standard deep-penetrating universal primer	For strengthening weak surfaces, increasing wear resistance and adhesion between the surface and coating. Surfaces: lightweight concrete, plaster, brickworks, gypsum etc. For indoor and outdoor application.		5 l	1	
				10 l	1	
23	"Classic - 4" Deep-penetrating anti-fungal primer	For destroying and preventing mold, fungus, bacteria, moss etc. on mineral surfaces. For indoor and outdoor works.		1 l	15	
				5 l	1	
				10 l	1	
24	"Classic - 5" Protection and repair hydrophobing primer	For long-term protection of concrete, brick, plaster etc. surfaces from moisture. For strengthening and making mineral surfaces water-repellent properties. The surface remains breathable after application. For indoor and outdoor works.		1 l	15	
				5 l	1	
				10 l	1	
25	"Classic - 6" primer concentrate	Used before finishing works, as well as an additive to dry cement and plaster mixes. Mixed in 5 liters of water. For indoor and outdoor works.		1 l	15	
26	"Classic - 7" Efflorescence washer - primer	For cleaning mineral surfaces (ceramic, tiles, shingles, production of silicate materials and concrete, masonry joints etc.) on building facades from salt contamination. Effectively removes efflorescence. Does not change structure color and surface. For outdoor works.		5 l	1	
				10 l	1	
27	"Builder - 1" Antifreeze-plasticizer	Plasticizer. Accelerator for concretes and mortars. Execution of work at low temperatures. Plasticizes, improves mobility and stability of solution.		1,2 kg	15	
				6,0 kg	1	
28	"Builder" Strengthening additive	For adding to cement mixtures, plasters, adhesives, masonry mortars in order improve their exploitation and technical characteristics: adhesion, elasticity, water- and frostresistance, strength. For indoor and outdoor works.		1,0 kg	15	
				5,0 kg	11	
				10,0 kg		







ADHESIVE COMPOSITIONS

29	"PVA - D" Construction adhesive	Extra strong and elastic. For bonding wooden and paper products, PVC flooring, fabric and cork. Can be used as an additive in building mortars and mixtures to increase strength, adhesion and plasticity. For indoor works only.		0,25 kg	35	
				0,50 kg	24	
				1,0 kg	15	
				2,5 kg	6	
				5,0 kg	1	
				10,0 kg	1	
				50,0 kg	1	
30	"PVA - D" Plasticized 51P dispersion	For bonding textile, printing, wood, furniture, shoe, leather and glass industry products.				

		For household adhesion manufacture. Can be used as an additive in construction mortars in order to give plasticity, water- and frost-resistance. Also to increase adhesion of a solution to a surface. Extraction remains (Dry) 51%.		5,0 kg 10,0 kg 50,0 kg	1 1 1	
31	"PVA - D" Plasticized 40P dispersion	For bonding textile, printing, wood, furniture, shoe, leather and glass industry products. For household glues manufacture. Additives in construction mortars in order to give plasticity, water- and frost-resistance. Also increase adhesion to solution base. Extraction remains (Dry) 40%.		5,0 kg 10,0 kg 50,0 kg	1 1 1	
32	"DREVISIN - D2" Adhesive for all type of wood	High quality. For cork wood, fiberboard, particle board, plywood, veneer, paper-layered plastic and cardboard. Moisture resistance D2. For indoor works only.		0,25 kg	35	
33	"DREVO STRONG - D3" Adhesive for all types of wood	Professional. For furniture, windows and other structures, parquet, plywood, fiberboard, particle board, veneer and cardboard. High cohesion with wooden surfaces subjected to static and dynamic loads. Moisture resistance D3. For indoor works only.		0,25 kg 0,5 kg 1 kg	35 24 15	


























34	"LIQUID NAILS" silicate adhesive	For construction materials, paper and cardboard. Glue for manufacturing acid-resistant and fire-resistance silicate masses. Impregnation of different type of wood and fabrics in order to impart density and fire resistance. Acts as hydro isolation additive for cement mortars. For indoor and outdoor works.		1,2 kg 2,2 kg 3,0 kg 5,0 kg 14 kg 50 kg	15 9 6 4 1 1	
35	"Acrylin - 3 LIQUID NAILS" adhesive	Highly adhesive. For attaching crown moldings and slabs made from expanded polystyrene, plastic, drywall, ceramic tile, wood, laminate, parquet, particle board, PVC and linoleum. Moisture resistance D3. For indoor and outdoor works.		1,5 kg	12	
36	"KS - D" Building, frost - resistant adhesive	Extra strong, highly adhesive and frost-resistant. For parquet, lenalium based on tiles, plasterboard and wooden products. For indoor and outdoor works.		0,95 kg 2,5 kg 4,5 kg 12 kg	12 1 1 1	
37	"Bustilat - D" Building adhesive	Acrylic. For parquet, linoleum based on tiles, wood, plasterboard, heavy and cork wallpaper, paper. For indoor works only.		1,2 kg 4,2 kg	12 1	
38	"ACRYLIN - 2" Mosaic adhesive	Professional. Extra strong. For mosaic, ceramic tiles, glass and ceramic borders. For indoor works only.		0,7 kg 1,5 kg 3,5 kg	24 12 4	
39	Glue for parquet «ACRYLIN P» D3	Glue for parquet, laminate surfaces and particle board. Based on styrene acrylic without solvents. Stable to brief exposure to water. Highly adhesive and fast dries. Odorless. For indoor and outdoor works.		2,5 kg 12 kg	4 1	
40	Adhesive for linoleum «ACRYLIN L»	Extra strong, universal glue for different type of linoleum (with and without base), PVC tiles, carpet coatings with foam or felt substrate for concrete, sand-cement base, plywood, fiberboard, particle board, OSB and others. Odorless. For indoor works only.		2,5 kg 6,0 kg 12 kg 60 kg	4 1 1 1	
41	Mastic adhesive "HATCH - 3"	For attaching decorative borders and slabs of expanded polystyrene and plasterboard, as well as embedding joints between them in dry and wet areas. For indoor works.		0,7 kg 1,5 kg 3,5 kg	24 12 4	
42	Decorative stone adhesive	SUPER ADHESION! For reliable long-term bonding of decorative natural and artificial stone on different surfaces				













	"Acrylin-5"	(minerals, wood, OSB, plasterboard, metal). For decorative stone electricity, bio and classic fireplaces (without direct contact with flame of decorative elements and adhesive joint). For jointing seams between decorative stones. Does not flow down on vertical surface. Moisture resistance D3. Solvent-free and odorless. Colors available: white. For indoor and outdoor works.		1,5 kg 3,5 kg 6,0 kg	12 4 1	
43	"Strong Contact" polyurethane foam adhesive	Extra strong. Exelent adhesion to porous and smooth surfaces. Stable to weather and temperature changes. Acts like Super glue for decorative elements from polyurethane and polystyrene foam and drywall.		0,7 kg 1,5 kg 3,5 kg	24 12 4	
44	Highly elastic adhesive «NEOPREN»	Extra strong construction glue. For laying rubber, gum, PVC - coatings, as well as linoleum and cork tiles on the prepared base. Suitable for underfloor heating. After drying, forms a durable and elastic joint that is resistant to mechanical stress and moisture. For indoor works only.		0,7 kg 1,5 kg 3,5 kg	24 12 4	
45	"Elite DRAKON" polymeric adhesive	The new formula of strength! Universal and frost-resistant. For gluing products from expanded polystyrene, parquet, mosaic parquet, wood (as well as cork), ceramics, floor carpeting surfaces, artificial leather and paper. For indoor and outdoor works.		0,2 l 0,4 l 0,8 l	40 30 20	
46	"Golden drakon" Polymeric adhesive	For gluing decorative products from expanded polystyrene and polyurethane, as well as products made of wood, ceramics, leather, carpeting and paper. For indoor and outdoor works.		0,2 l 0,4 l 0,8 l	40 30 20	









47	Polymeric adhesive «Titan' Power»	Polymeric glue, high adhesive, heat-resistant, based on highquality synthetic tar. For gluing products from expanded polystyrene, parquet mosaic, wood, cork, ceramic, floor surface, natural and artificial leather, paper and fabric. For indoor and outdoor works.		0,2 l 0,4 l 0,8 l	40 30 20	
48	Water-polymeric adhesive «ECO DRAKON»	Glue based on water-soluble polymer. Does not contain organic solvents. For gluing products from expanded polystyrene, polyurethane foam, wood, cork, floor carpets, leather and paper. One of the surfaces must be absorbent. For indoor works only. Semitransparent.		0,2 l 0,4 l 0,8 l	40 30 20	
49	Frost-resistant universal glue «Highly Viscous»	Glue based on synthetic polymer. After drying, forms waterproof glue seam that is stable to mechanical stress. High adhesive, heat-resistant and frost-resistant. Does not flow down on vertical surfaces. For gluing in various combinations of products: polystyrene, polyurethane, parquet, wood, ceramic, porcelain, felt, fabric, foam rubber, as well as cork, bamboo wallpaper, cardboard and paper. For indoor and outdoor works.		0,8 l 2,0 l	18 6	
50	Glue for floor coverings «DivoFix»	Glue fixation for all kinds of flexible floor coverings. Water and frost resistant. Suitable for gluing of carpet and all type of linoleum. After drying, forms a waterproof adhesive seam to mechanical influences. High adhesion. Color available: white.		0,25 l 0,50 l	35 24	
51	Putty for windows «HATCH- 1»	For sealing joints between glass and wood by wooden parts. Prevents the formation of mold. You can paint it. Water and freeze resistant.		0,4 kg	30	
52	Grout "SEAM - 1" Dry mortar	For filling joints between ceramic (wall, floor), marble and concrete plates. For indoor and outdoor works.		1,0 kg	15	

ACRYLIC WATER BASED PAINTS

53	Paint «Interior»			1,4 kg	12	
----	------------------	--	--	--------	----	--

		<p><i>Water-dispersion. For interior work on any type of porous surfaces. Resistant to dry abrasion.</i> <i>Spread rate: 6-8 m²/l (180 g/m²) in one layer.</i> <i>Colors available: white.</i> For indoor works only.</p>		3,0 kg	1	
				5,0 kg	1	
				7,0 kg	1	
				14,0 kg	1	
				60,0 kg	1	
54	Paint «Aqua-acryl»	<p><i>Acrylic. For interior work on any type of surfaces, as well as wallpaper for painting. Resistant to water washing.</i> <i>High coverage.</i> <i>Spread rate: 7-8 m²/l (180 g/m²) in one layer.</i> <i>Colors available: show white.</i> For indoor works only.</p>		1,4 kg	12	
				2,8 kg	4	
				4,2 kg	4	
				7,0 kg	1	
				15,0 kg	1	
				60,0 kg	1	
55	"7-Semerochka" Silky-matte paint	<p><i>Water-dispersion. For painting surfaces that needs high resistance to washing and wearing: kitchens, vestibules, stairwells, offices, schools, hospitals, restaurants etc. Excellent adhesion to plaster, concrete, brick and other mineral surfaces. As well as gypsum board, fiberboard, particle board and textured surfaces. Spread rate: 10 m²/l (150-200 g/m²).</i> For indoor works only.</p>		1,4 kg	12	
				2,8 kg	4	
				4,2 kg	4	
56	Paint "FASAD – LUX"	<p><i>Acrylic. For high-quality protection and decoration painting inside and outside of building. On any type of porous surfaces: brick, concrete, cement, plaster and wood (except floors).</i> <i>Spread rate: 10-12 m²/l (150-200 g/m²).</i> <i>Colors available: white and beige.</i></p>		1,4 kg	12	
				2,8 kg	4	
				4,2 kg	1	
				7,0 kg	1	
				15,0 kg	1	
				60,0 kg	1	
57	Paint for radiators	<p><i>For protective and decorative painting of radiators and elements of heating systems in residential and commercial buildings. Creates heat-resistant (up to 95°C) coat. Fast drying. Does not yellow.</i> <i>Colors available: matte white.</i></p>		0,5 kg	18	
				0,9 kg	18	
58	Paint for gas pipes	<p><i>Acrylic. For protective coating of gas pipes and gas-mains. After drying, forms varnish-like paint coating. Weather and ultraviolet radiation resistant. Fast drying, excellent covering ability and adhesion to metal. Economic. Does not contain organic solvents. Colors available: yellow.</i> For indoor and outdoor works.</p>		1,4 kg	12	
				2,8 kg	4	
				4,2 kg	1	

59	Blocking paint "STOP NIKOTIN"	<p><i>High-quality latex based paint for first and repair coating of walls and ceilings that require high durability to washing (office and residential buildings, hotels, restaurants, shops, health care, preschool and educational institutions, public buildings and chemical laboratories). After drying, forms a layer of paint that blocks nicotine stains, unpleasant odors, soot, rust etc. For indoor works only.</i></p>		1,4 kg	12	
				2,8 kg	4	
				4,2 kg	1	
				7,0 kg	1	
60	"Termos N" interior paint for heat protection	<p><i>High-quality paint for walls and ceilings, which reduces heat loss to 20%. Paint consists of metal pigment that effectively reflects heat into the room. Dried layer of paint resistant to abrasion and moisture. Excellent adhesion to building materials. Colors available: white.</i> For indoor works only.</p>		1,4 kg	12	
				2,8 kg	4	
				4,2 kg	1	
				7,0 kg	1	
61	Heat protection paint «Termos N»	<p><i>High-quality paint for protection against growth of fungus and algae. After drying, forms protective layer that fixes conditions for growth of fungus, molds and algae. Persistent to weather and moisture resistant. Excellent adhesion to building materials. Does not contain harmful biocides.</i> <i>Colors available: white.</i> For outdoor works.</p>		1,4 kg	12	
				2,8 kg	4	
				4,2 kg	1	
				7,0 kg	1	

62	Varnish for stone	Semi-mat paint for long-term protection against weatherproof, high wear resistance, decorative finishing of mineral surfaces (natural and artificial stone, decorative tiles, decorative brick elements, concrete, plaster and granite). Fast drying, does not contain solvent. For indoor and outdoor works.		0,9 l	12	
				2,0 l	8	
				5,0 l	1	
PROTECTION OF WOOD						
63	Drying oil	Oxidized drying oil modified with siccativ. Excellent penetrates in wood pores, stresses product structure, has high wear resistance and excellent pacifier.		0,5 l	24	
				1,0 l	12	
64	Glossy varnish for wood	To cover the wooden surfaces. After drying, forms a transparent coating and solid elastic film. Does not flow down from vertical surfaces. Weather resistant, water-repellent, fast drying. For indoor and outdoor works.		0,9 l	12	
				2,0 l	4 1	
				5,0 l		
65	Mat Varnish for wood	To cover the wooden surfaces. After drying, forms a transparent coating and solid elastic film. Does not flow down from vertical surfaces. Weather resistant, water-repellent, fast drying. For indoor and outdoor works.		0,9 l	12	
				2,0 l	4	
				5,0 l	1	
66	"Silk" varnish for cork and bamboo	Intended for cork and bamboo products: parquet, curtains, blinds, furniture, wallpaper etc. Protection against abrasion, adhesion of dirt, moisture absorption and destructive action of ultraviolet rays (loss of color). Gives surface: water-repellent ability, silky coat, enhances color saturation, highlights and emphasizes the natural structure of cork and bamboo.		0,9 l	12	
67	Dry mixture for wood impregnation and protection "A1"	Deep penetrating. For impregnation of bearing structures and wooden elements before applying varnish or paint. After impregnation, wood becomes darker. Lifetime up to 50 years. Can be diluted with water to 10 liters. For indoor and outdoor works.		0,9 kg	12	
				4,5 kg	1	
68	Ready to use treatment for wood protection "A2"	Deep penetrating. For impregnation of any timber before applying varnish to. Protection against fungal infections. Does not change the color of the wood. For indoor and outdoor works.		1,0 l	15	
				5,0 l	1	
69	Concentrate for timber treatment and protection «A 3»	Deep penetrating. For impregnation of any timber before applying varnish to. Protection against fungal infections. Does not change the color of the wood, also does not contain solvents. Diluted with water in a ratio of 1.7 to 1:14. For indoor and outdoor works.		1,0 l	15	
				2,0 l	4	
				5,0 l	1	

WALLPAPER ADHESIVES






ACRYLIC, READY FOR USE

70	For heavy wallpaper "AQUA - STRONG"	For premises with high humidity. For fiberglass, tufted, textile, jute, grass, reed, vinyl and acrylic wallpaper.		5,0 kg	1	
				10,0 kg	1	
				15,0 kg	1	
71	For wallpaper joints "AQUA - STRIP"	For gluing joints of all kind of wallpaper and borders on paper basis. For fast repair delaminated wallpaper.		0,25 l	35	
72	For cork and bamboo wallpaper "ACRYLIN- 1"	Glue for natural wallpaper made of bamboo, cork, tufting, plywood, jute, reed and grass. Multicolor.		0,7 kg	24	
				1,5 kg	12	
				3,5 kg	4	



STARCH-BASED, INSTANT, HIGH PURITY

73	"EXPERT INDICATOR"	For all types of wallpaper also on flizelin basis. Контролируем равномерность нанесения клеевого слоя. 12 rolls 15 rolls		250 g	28	
				300 g	28	
74	"SPECIAL UNIVERSAL"	For vinyl, flizelin and blank wall paper. 6 rolls 14 rolls		200 g	28	
				300 g	28	
75	"MASTER VINYL"	For light, washable, heavy, vinyl and flizelin wallpaper. 12 rolls		250 g	28	
76	"FLIZELIN "	For vinyl, flizelin and blank wall paper. 40 m² 55 m²		200 g	28	
				300 g	28	
77	"PREMIUM EXCLUSIVE "	For all types of wallpaper also on flizelin basis. Concentrated. 15 rolls		300 g	28	
78	"EXCLUSIVE"	For all types of wallpaper: light, washable, heavy and vinyl. 12 rolls		200 g	28	
79	"STYLE" adhesive for billboards and posters	For outdoor work (Winter-Summer). High adhesion to metal, glass, wood and cement. For 6 standard (20m²) big boards.		1000 g	6	







QUICK-DISSOLVING CMC

80	"SUPER - MAX"	For light and heavy wallpaper. Stable to cement. 12 rolls		350 g	28	
81	"MODERN"	For light, washable, heavy and vinyl. 12 rolls		300 g	28	
82	"ETUDE"	For light, washable, heavy and vinyl. 12 rolls		300 g	32	
83	"CMC - N" 200 g + 80 g free	For light and washable wallpaper. Based on synthetic high molecular compounds. 10 rolls		280 g	28	
84	"CMC - N"	For light, washable wallpaper and oilcloth. 6 rolls		125 g	60	

CMC FAST DISSOLVING WITH A HIGH DEGREE OF WHITENESS

85	"MOMENTAL"	For light, washable, heavy, vinyl. 10 rolls		200 g	30	
				200 g	28	
86	"Gluten"	Glue for all type of photowallpaper, made of premium cotton. Due to its soft elastic structure solution, it facilitates photowallpaper gluing. 22 m2		100 g	28	

CMC CONCENTRATED, FINELY DISPERSED

87	"CMC - N" + PVA 5 – 6 rolls	For light, heavy, vinyl. With the addition of PVA. 5-6 rolls		200 g	29	
88	"CMC - N" + PVA 10 – 12 rolls	For light, heavy, vinyl. With the addition of PVA. 10-12 rolls		200 g	29	
GARDENNING						
89	Lime wash «MICHURINKA » dry mix	Universal. Bacterial protection of trees and shrubs from pests and diseases. For painting buildings, fences, sheds and cellars. For outdoor works.		1,0 g 2,0 g 3,0 g	12 6 4	
90	Paint «MICHURINKA - 2» ready-made	For painting the trunks of fruit trees and bushes. For decorative purposes and for protection against pests and sunburn. Protects against extreme temperatures in autumn and spring. For outdoor doors.		1,3 g 2,8 g 4,2 g 7,0 g 14,0 g	12 6 4 1 1	
91	Grafting compound «MICHURINKA-3»	For healing of trees bark, damaged shrubs by rodents, cossidaes, bacterial and fungal cancer. For treatment of thermal and water damages. It has healing and antimicrobial features. For outdoor works.		80 g	40	
92	«BORDO mixture»	In order to combat fungal diseases and disinfect trees wounds. For outdoor works.		220 g	30	
PRODUCTION OF PET-bottles						
93	PAT - bottle	Bottles intended for food packing, cosmetics, household and automobile chemicals, paints and solvents.		0,25 l 0,5 l 1,0 l		